



Catalog Number	
Project	Type

FEATURES & SPECIFICATIONS

APPLICATION — The CES Canopy light was designed for low level lighting under storefront awnings, or any surface mount general lighting application. The welded seams provide a smooth constructed look that can be integrated into any design concept. This fixture is perfect when a finished, rather than industrial appearance is needed.

CONSTRUCTION — The fixture is constructed of .12" thick extruded aluminum with a welded seam. The hinged door frame is constructed of extruded aluminum with mitered corners to fit the glass lens. A Polyethylene Foam gasket is used for a watertight seal.

FINISH — A Super Durable Polyester powder coat finish is electrostatically applied in our state of the art paint facility. Standard colors available: Black, Bronze, US Green, White. Custom colors available upon request.


OPTICAL SYSTEM — High quality faceted aluminum reflector designed around a vertical lamp orientation. Flat glass, flat prismatic, and drop lenses available.

ELECTRICAL SYSTEM — Available in 150W, 250W, and 400W pulse start metal halide. Provided with a 4KV pulse rated socket or GX24q socket assembly. Single back side conduit entry. Fixtures are available with a 26W-42W CFL, 50W-175W Metal Halide, and 35W-150W HPS lamp and ballast system. Each 60HZ CWA multi-tap, 480V, or Fluorescent ballast is pre-wired and installed for convenience.

MOUNTING — Permanently mounted via four .25" mounting holes and hardware pack provided by Techlight. Two (2) .88" conduit entries are provided



Small Extruded Canopy CES SERIES



Series	Housing Height	Length & Width
CES	7.06"	13.63" x 13.63"

ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

Example: **CES175M-MT-F-WH**

CES					
Series	Wattage/Source	Voltage	Lens	Pulse-Start	Finish
CES	26FL 26W Fluorescent ² 42FL 42W Fluorescent ² 50M 50W PS Metal Halide 70M 70W PS Metal Halide 100M 100W PS Metal Halide 150M 150W PS Metal Halide 175M 175W Metal Halide 35H 35W High Pressure Sodium 50H 50W High Pressure Sodium 100H 100W High Pressure Sodium 150H 150W High Pressure Sodium	MT Multi-Tap ¹ 480 480V 120 120V	F Flat Glass FP Flat Prismatic D Drop Lens	PS Pulse-Start	BK Black BZ Bronze GR US Green WH White SP Special ³

NOTES

- 1 Multi-Tap is 120/208/240/277V wired 277V.
- 2 Fluorescent models available in 120V only and with a drop lens only.
- 3 Custom RAL color matching is available. Contact your Techlight sale representative for additional information.