


## ELV300

### 300W Low Voltage Enclosure



## ORDERING INFORMATION

Description	Part Number
300W 120V INPUT XFMR	ELV300
*Comes standard in black finish	

## DESIGN

The ELV300 was designed as an economical and durable transformer enclosure. It features a fully encapsulated 300W low voltage transformer. Keyhole mounts are provided on the backside of the enclosure for quick and secure mounting. Custom finishes available upon request.

## ACCESSORIES



MECHANICAL TIMER  
TLTN111



LOW VOLTAGE WIRE  
PW122LV (12-2)  
PW102LV (10-2)



PHOTOCELL  
P2000PC-LVENC<sup>1</sup>



PHOTOCELL EXTENSION  
CORD  
PCCORD-6<sup>1</sup> (6')  
PCCORD-8<sup>1</sup> (8')

## TECHNICAL INFORMATION

Constructed from formed aluminum. A 6-ft 16/3 SJ TW cord with a grounded straight blade plug comes standard. Field installable timer and photocells are available. Each unit is provided with two 3/4" and one 1/2" knockouts on the underside for low voltage exit, and one 1/2" knockout on each side for accessory mounting. Color coded secondaries include 12V, 12V, 13V, 14V, 15V, 15V, 24V, and COM output taps.

Notes: 1-Item is provided with quick connects for installation.