



Catalog Number	
Project	Type

FEATURES & SPECIFICATIONS

APPLICATION — The TLP36W Low Voltage Well Light was designed as a low profile in-ground incandescent well light. It can stand up to the corrosive forces of water, soil, and time. Safety grills are available for a pleasing finish and safety.

CONSTRUCTION — The fixture made from stamped brass and copper with stainless steel hardware. Single piece black ABS mounting sleeve with angle cut comes standard. Comes with 3' of 18-2 low voltage wire and a low voltage connector.


OPTICAL SYSTEM — The lamp can be rotated 360° and can be tilted up to 45° from vertical. It can be used with up to 50W PAR36 Incandescent lamps. Spring loaded clips allow for easy lamp replacement.

ELECTRICAL SYSTEM — They are designed to be operated with a standard 12V transformer.

MOUNTING — The TLP PAR36 Well Light is an in-ground fixture and should be installed with back fill according to the Techlight installation instructions. Provides excellent water drainage when installed on a gravel bed. Comes with 3' of 18-2 low voltage wire. Gelpak provided for conduit installation.



PAR36 Well Light TLP SERIES



Series	Housing Height	Diameter
TLP	8.50"	Ø5.50"

ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

TLP		Well Light		Lamp		Sleeve	
Series							
TLP		36W	PAR36 Well Light	Blank	No Lamp (ordered separately)	Blank	Short Sleeve (8.50")
				L-36W	36W 12V PAR36 Wide Flood	L	Long Sleeve (10.875")

Example: **TLP36W-L**

Accessories (Order as separate line items)

I25P36VNSP12	25W/12V PAR36 Very Narrow Spot	I50P36VNSP	50W/12V PAR36 Very Narrow Spot
I25P36NSP12	25W/12V PAR36 Narrow Spot	I50P36NSP	50W/12V PAR36 Narrow Spot
I25P36WFL12	25W/12V PAR36 Wide Flood	I50P36FL	50W/12V PAR36 Wide Flood
I36P36VNSP12	36W/12V PAR36 Very Narrow Spot	S126	Angled Cut End, Short Sleeve Guard
I36P36WFL12	36W/12V PAR36 Wide Flood	S125	Straight Cut Sleeve End Guard

TLP PAR36 Well Light

ADDITIONAL FIXTURE ACCESSORIES

S126

Angled Cut End, Short Sleeve Guard



S125

Straight Cut Sleeve End Guard



WARNING: Maintenance performed including the replacement of LED bricks while power is still supplied to the luminaire may result in system failures and will void the warranty.



Techlight, Inc.
2707 Satsuma Drive
Dallas, TX, 75229
Phone: 214-350-0591, 800-225-0727, Fax: 214-350-9137
www.techlight.com