


# TH SERIES

## 16" Low Bay



# ORDERING INFORMATION

|              |                  |
|--------------|------------------|
| 150W HPS MT  | TL16M-17-9- (A)  |
| 175W MH MT   | TL16M-1-1- (A)   |
| 175W PSMH MT | TL16M-3-2- (A)   |
| 250W MH MT   | TL16M-5-3- (A)   |
| 250W PSMH MT | TL16M-7-4- (A)   |
| 250W HPS MT  | TL16M-19-10- (A) |
| 320W PSMH MT | TL16M-9-5- (A)   |
| 350W PSMH MT | TL16M-11-6- (A)  |
| 400W MH MT   | TL16M-13-7- (A)  |
| 400W PSMH MT | TL16M-15-8- (A)  |
| 400W HPS MT  | TL16M-21-11- (A) |

### (A) Hook, Cord, and Plug

- 0 - None
- 1 - Hook Only
- 2 - 6' Cord Only
- 3 - 120V HCP
- 4 - 220/240V HCP
- 5 - 277V HCP
- 6 - 480V HCP

# DESIGN

Techlight's line of low bays was designed for light manufacturing, warehouse, retail, assembly lines, or production environments. The acrylic drop reduces shadows and provides a wide uniform distribution. Made for low mounting heights.

# SHIELDS



# ACCESSORIES



**MOUNTING HOOK**  
THBH



**18" RIGID PENDANT**  
THBSTEM18



**6' PJ16/3 CORD**  
THBHC6



**12" REFLECTOR SAFETY CHAIN**  
THBSC1



**SWIVEL PENDANT MOUNT**  
THBSPM




**6' BALLAST POD SAFETY CHAIN**  
THBSC6

# PHOTOMETRICS

SEE INSIDE REPORT  
PHOTOMETRIC FILENAME: 147L16M10P10M16LIES

FILE:MT.GRAPH



Model: 147L16M10P10M16LIES  
#1 - Vertical Plane Through Vertical Angle (V) - Vertical Plane = 42.5  
#2 - Horizontal Plane Through Vertical Angle (V) - Horizontal Plane = 42.5

# TECHNICAL INFORMATION

Heavy duty die cast aluminum housing with a white polyester powdercoat finish. Splice box for direct hard wire, hook, cord, and plug assembly, or pendant mount. White spun aluminum reflector and acrylic drop lens. Available in 175W-400W Metal Halide and 150W-400W High Pressure Sodium light sources.

LOW BAYS