


R-SERIES

Small Copper Bullet



DESIGN

The R2LWC Bullet Light was designed to set the industry standard for copper landscape bullets. Their sturdy copper construction allows them to be used in harsh environments. The various finishes available allow this fixture to blend seamlessly into the aesthetics of any landscape design.

ACCESSORIES



BRASS TREE BASE
B06



1/2" CONDUIT BASE
B02



1/2" Hub with Ground
Wire
B10



20" x 2 1/2" Mounting
Stake
LMS



20" x 2 1/2" Mounting
Stake with Brass Cap
LMSB



BRASS JUNCTION BOX
TLSBBJB

ORDERING INFORMATION

35W MH PAR20 NFL, DOWN SHIELD	R2LWC-1-2-2-11-(A) ¹
35W MH PAR20 NFL, UP SHIELD	R2LWC-2-2-2-11-(A) ¹
35W MH PAR20 SP, DOWN SHIELD	R2LWC-1-2-3-11-(A) ¹
35W MH PAR20 SP, UP SHIELD	R2LWC-2-2-3-11-(A) ¹
50W MV R20, DOWN SHIELD	R2LWC-1-2-1-7-(A) ²
50W MV R20, UP SHIELD	R2LWC-2-2-1-7-(A) ²
50W QUARTZ NFL, DOWN SHIELD	R2LWC-1-2-4-0-(A)
50W QUARTZ NFL, UP SHIELD	R2LWC-2-2-4-0-(A)
50W QUARTZ NSP, DOWN SHIELD	R2LWC-1-2-5-0-(A)
50W QUARTZ NSP, UP SHIELD	R2LWC-2-2-5-0-(A)

(A) Finish

1 - Natural Copper	5 - Black
2 - Brown Patina	6 - Bronze
3 - Flemish Patina	7 - OD Green
4 - Gray Patina	8 - White
	9 - Special

SHIELDS



SMALL COPPER DOWN
SHIELD
S65



SMALL COPPER UP
SHIELD
S66



SMALL COPPER DOWN
SHIELD WITH LENS
S67



SMALL COPPER UP
SHIELD WITH BLUE
LENS
S68



SMALL HONEYCOMB
LOUVER
S80

TECHNICAL INFORMATION

Constructed of spun copper, it comes standard with a 1/2" threaded knuckle mount and 4KV pulse rated medium base socket. Light sources are available in 50W Mercury Vapor, 35W Metal Halide, or 50W Incandescent. The fixture can be finished with a durable polyester powdercoat paint, left unfinished to patina naturally, or provided with a factory applied patina finish.

Notes: 1-Fixture must be mounted within 10' of ballast enclosure.
2-Fixture may be provided with a Metal Halide ballast designed to operate a Mercury Vapor lamp.