



Catalog Number	
Project	Type

FEATURES & SPECIFICATIONS

POLE — The SS2P Series are 2-Piece Poles designed for easy installation, convenient storage, and simple handling. The pole shaft is fabricated from hot rolled carbon steel having a minimum yield of 55,000 PSI and conforms to ASTM A500 grade C requirements. The shaft construction is formed steel welded longitudinally. The 2 pole pieces interlock via a square splice plug welded to the top pole section and secured into the lower section using set screws. The hand hole is located 1' above the pole base. A ground lug is provided standard.

ANCHOR BASE — The anchor base is fabricated from a structural quality hot rolled carbon steel plate that has a minimum yield strength of 36,000 PSI. The anchor base telescopes the pole shaft and has a circumferential weld on the top and bottom.


BASE COVER — A full base cover is provided which encapsulates the base plate and anchor bolts to provide a clean transition from pier to pole.

FINISH — A Super Durable Polyester powder coat finish is electrostatically applied in our state of the art paint facility. Standard colors available: Black, Bronze, US Green, White. Custom colors available upon request.

15' Steel 4" Square 2-Piece Pole TOTE-EM MODULAR POLE SERIES

Technical Data

Nominal Pole Height	15'-0"
Shaft Dimensions	Bottom: 8' x 4", 86 lbs Top: 7' x 4", 61 lbs
Wall Gauge	11 Gauge
Bolt Circle	8.0"
Bolt Size	3/4" x 18" x 3"
Base Plate Dimensions	8.0" sq. x .75" thk.
Est. Shipping Weight	147 lbs




Max EPA (1.3 Gust)


115 mph	14.6
120 mph	13.2
130 mph	11.0
140 mph	9.2

For Reference Only: The ASCE 7 Hazard Tool is the official source of information for pole selection when identifying wind speed zone limits within North America.

<https://asce7hazardtool.online/>



TL-GFIA - Ground Fault Receptacle



ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

Example: **SS2P 15 4 11 BZ T238**

SS2P

Series	Pole Height	Pole Size	Pole Gauge	Color	Mounting
SS2P	15 15' Nominal	4 4" Square	11 11 Gauge	BK Black BZ Bronze WH White GR US Green SP Special	T238 2-3/8" OD Tenon (Standard)

NOTE: ANCHOR BOLT KITS MUST BE ORDERED AS A SEPARATE LINE ITEM. EACH KIT IS PROVIDED WITH A RIGID TEMPLATE FOR INSTALLATION. SEE ACCESSORIES FOR KIT PART NUMBERS. PLEASE NOTE ON PURCHASE ORDER IF ANCHOR BOLTS AND TEMPLATES ARE TO BE PRE-SHIPED.

Accessories (Order as separate line items)

KAB3418G08R	AB Kit (4) 3/4" x 18" Galvanized Bolts and Rigid Template	PHH¹	Additional Hand Hole
TLGFIA²	Ground Fault Receptacle		

NOTES

- Please note location for additional hand hole when ordering. See Drilling Locations diagram for location designations.
- The TLGFIA (Ground Fault Circuit Interrupter) comes with a die cast aluminum in-use cover.