



Catalog Number	
Project	Type

FEATURES & SPECIFICATIONS

APPLICATION — The CLSV Canopy light was designed as an easy to install, economical, and long lasting canopy light. The compact size and wide array of available wattages allows this fixture to fit into a multitude of mounting applications. The vertical burn lamp position makes this fixture efficient and precise.

CONSTRUCTION — Constructed with a die cast aluminum housing with a powdercoat finish. It is fully gasketed to a clear polycarbonate lens assembly to provide weather resistant protection.

FINISH — A Super Durable Polyester powder coat finish is electrostatically applied in our state of the art paint facility. Standard colors available: Black, Bronze, US Green, White. Custom colors available upon request.



OPTICAL SYSTEM — Patterned clear vandal resistant polycarbonate lens. White reflector. Vertical lamp position for optimum efficiency and lamp life. Type V (360°) photometric pattern.

ELECTRICAL SYSTEM — Available in 50W thru 200W pulse-start metal halide, 175W standard metal halide, and 50W thru 150W high pressure sodium. Comes standard with a vertically mounted 4KV pulse rated socket. Each 60HZ CWA multi-tap¹ or 480V ballast is pre-wired and installed for convenience.

MOUNTING — Housing is equipped with two side conduit entries and one top conduit entry. The fixture comes standard with a “quick mount”. The fixture is designed to hang independently while being installed. This frees the installers’ hands to make critical wire connections with speed and ease. Designed to mount directly to a standard 4” junction box.



Vertical Burn Die Cast Canopy CLSV SERIES



Series	Housing Height	Length & Width
CLSV	11.75"	12.45" x 12.45"

ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

Example: **CLSV5A1-BZ**

CLSV							
Series	Wattage/Source	Voltage	Pulse-Start	Finish			
CLSV	1A 50W PS Metal Halide 1B 50W High Pressure Sodium ² 2A 70W PS Metal Halide 2B 70W High Pressure Sodium 3A 100W PS Metal Halide 3B 100W High Pressure Sodium 4A 150W PS Metal Halide 4B 150W High Pressure Sodium 5A 175W Metal Halide 6A 200W PS Metal Halide	1 Multi-Tap ¹ 2 480V	PS Pulse-Start	BK Black BZ Bronze GR OD Green USG US Green WH White SP Special ³			

NOTES

- 1 Multi-Tap is 120/208/240/277V wired 277V.
- 2 50W High Pressure Sodium model is only available in 120V NPF. Order using the “1” voltage designation.
- 3 Custom RAL color matching is available. Contact your Techlight sale representative for additional information.