

## **FEATURES & SPECIFICATIONS**

FEATURES - Energy-efficient LED technology. Decals and template provided for chevron directional indicators. UL listed for damp locations & meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.

**CONSTRUCTION** — Premium-grade, extruded aluminum housing (also available in black or white powder coated).

ELECTRICAL SYSTEM - Dual 120V/277V voltage. Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing. LVD (low voltage disconnect) prevents battery from deep discharge. Long-life, maintenance-free, rechargeable NiCd battery (B Model). Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination. Fully automatic solidstate, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours.

**MOUNTING** — Die-cast aluminum mounting canopy included-provides top, end or back mount convenience.

**ILLUMINATION** — Ultra-bright, energy efficient, long-life Red or Green LED. UV-stablilized ultra-clear acrylic edgelit panel provided consistent, uniform illumination.


WARRANTY - Five Year Warranty on all electronics and housing. Batteries are pro-rated warranted for 5 years.

Catalog Number	
Project	Туре



## **LED Edgelit Exit Sign ELE SERIES**





Series	Housing Height	Length & Width
ELE	11.125"	13.00" x 1.75"

## ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

ELE Series ELE

**Letter Color** 

R Red Green

G

**Number of Faces** 

Single Face

Double Face1

**Panel Color** 

C Clear M Mirror

(Silver Mylar) White (White Mylar) **Housing Color** 

Example: **ELER2WW** 

W White В Black

Anodized Aluminum **Battery** 

Blank AC Only B Battery Back-Up

**Options** 

SD Self Diagnostic

2C Dual Circuit<sup>2</sup>

- Double Face model is only available with Mirror or White Panel Colors.
- Only one "hot" circuit at a time