TECHLIGHT
INNOVATION IN ILLUMINATION

L2PCS SERIES

GEN 2 LED Petroleum Scottsdale Retrofit

Catalog Number	
Project	Type

SERIES	HOUSING HEIGHT	LENGTH & WIDTH
L2PCS	1.05”	12.75” x 12.75”

FEATURES & SPECIFICATIONS

APPLICATION — The high performance luminaire is designed for petroleum station canopy applications where long life, low maintenance, and consistent color rendering is required. All areas with limited accessibility due to fixture location or where heavy pedestrian or vehicle traffic makes maintenance difficult are ideal applications such for this fixture.

CONSTRUCTION — The heavy duty LED housing is constructed of cast aluminum. The mounting box is constructed of .063” thick sheet aluminum with a welded seam. The hinged door frame is constructed of .093” sheet aluminum. An EPDM foam and silcone rubber gasket is used for a watertight seal.

FINISH — A Super Durable Polyester powder coat finish is electrostatically applied in our state of the art paint facility. Standard colors available: White. Custom colors available upon request.

OPTICAL SYSTEM — Light is directed through a clear, flat tempered glass lens providing a uniform and symmetrical light pattern.

ELECTRICAL SYSTEM — Available in 5000K Cool White and 4000K Neutral White (+/- 150K) color temperatures propagated with LG Innotek 3030 LED’s. Minimum 80 CRI. Available with 90-300V 50/60 Hz. LED’s rated over 50,000 hours (TM21 Cal- culated L70) at 25°C ambient temperature with available 1250mA operation. Additional drive current and lumen output options available, consult factory. Lumen Maintenance >97% at 50K hrs. 347V and 480V input options available. Standard 0-10V dimming. Driver provided with integral 4kV surge protection that meets IEEE C62.42.2-2002. 10kV Surge Suppressor standard. Built-in Active PFC Function. LED Power Supply conforms to UL1310 Class 2 and UL8750 standards and is IP67 rated for wet locations.

MOUNTING — The fixture can be easily installed by one person. It may be mounted into a 12” or 16” deck pan. Door/LED assembly utilizes quick release hinges to allow the fixture body to be mounted first using 4 Pan Truss screws. Door/LED assembly may then be attached to the body and wiring connections made. A silcone sponge gasket and clamping plate is installed from the top of the canopy to prevent water intrusion. Incoming power connections can then be made inside a wet location juntion box (provided by others).

LISTINGS — ETL listed for wet locations (IP64). Meets US and Canadian safety standards. -40°C to 40°C ambient operation. RoHS Compliant.

ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

EXAMPLE:
L2PC S CW G M 1 WH

L2PC						
SERIES	MOUNTING	COLOR TEMP	OPTICS	DRIVE CURRENT[3]	VOLTAGE	FINISH
	S = Scottsdale Retrofit	**CW** = Cool White (5000K) **NW** = Neutral White (4000K)	**G** = Symmetric with Flat Tempered Glass Lens **AS** = Asymmetric with Flat Tempered Glass Lens	**M** = 1250 mA	**1** = Multi-Volt[1] **2** = 480V **3** = 347	**WH** = White **SP** = Special[2]

NOTES

1 = Multi-Volt is an auto ranging power supply from 100V to 300V input.

2 = Custom RAL color matching is available. Contact your sales representative for additional info.

3 = Consult factory for additional drive current options.

PROUDLY BUILT BY AMERICANS For Americans IN THE USA Techlight supports American families making quality products everyday.

www.techlight.com

L2PCS GEN 2 LED Petroleum Scottsdale Retrofit

FIXTURE DIMENSIONS

Dimensions shown are for fixture bodies only. Mounting options must be ordered separately.



LUMINAIRE CHARACTERISTICS

Drive Current*	Color Temp	Delivered Lumens Symmetric	Delivered Lumens Asymmetric	System Wattage	L70 @ 25°C	Amperage Draw			
						120V	208V	240V	277V
1250 mA	CW	14266	12125	132W	>50K	1.10 A	.63 A	.55 A	.48 A

*Consult factory for additional drive current and lumen output options.

PHOTOMETRICS

IES INDOOR REPORT PHOTOMETRIC FILE NAME: L2PCSCWGM1

1250mA, Cool White, Symmetric

132W L2PC Canopy
Color Temperature: 5,000 K



TECHLIGHT
PHOTOMETRIC FILE NAME: L2PCSCWGM1
PETROLEUM CANOPY SYMMETRIC

Horizontal Footcandles
Scale: 1 Inch = 15Ft.
Light Loss Factor = 1.00
Lumens Per Lamp = N.A. (absolute photometry)
Luminaire Lumens = 14266
Mounting Height = 18.00 Ft
Maximum Calculated Value = 17.279 Fc
Arrangement: Single

IES INDOOR REPORT PHOTOMETRIC FILE NAME: L2PCSCASM1

1250mA, Cool White, Asymmetric

132W L2PC Canopy
Color Temperature: 5,000 K



TECHLIGHT
PHOTOMETRIC FILE NAME: L2PCSCWASM1
PETROLEUM CANOPY ASYMMETRIC

Horizontal Footcandles
Scale: 1 Inch = 20Ft.
Light Loss Factor = 1.00
Lumens Per Lamp = N.A. (absolute photometry)
Luminaire Lumens = 12125
Mounting Height = 18.00 Ft
Maximum Calculated Value = 20.19 Fc
Arrangement: Single

WARNING: Maintenance performed including the replacement of LED bricks while power is still supplied to the lumenaire may result in system failures and will void the warranty.

TECHLIGHT
INNOVATION IN ILLUMINATION
2009 Mckenzie Drive Suite 110 I Carrolton, TX 75006 I PH: 800.225.0727 www.techlight.com

All dimensions and specifications are subject to change without notice.